

IP Camera		
Model		IPS-118X-IR
Version		1.0
Image Sensor		
Sensor		1/3" Aptina
Pixel Size, µm		3.75x3.75
Resolution, points@fps	Main stream	1280x960@30, 1280x720@30
	Sub stream	704x576@30
Day/Night mode		Auto/Color/Black&White
Sensitivity, Lux/Iris		Color 0.01Lux@F1.2, Black/White: 0.001 Lux@F1.2
Dynamic range WDR, dB		69
S/N ratio, dB		44
Video functions		AEC, AGS, AWB, ABF, ABLC, OSD, PrivacyMasks
Codec profile	H.264	Baseline / Main / High
Exposure mode, s	Auto	1/50-1/10000
	Manual	0.256-65.536
Bitrate Type, kb/s	Constant	1024-5120
	Variable	Worst/Worse/General/Good/Better/Best
Lens		
Focal length, mm		4.7-84.6
Optical zoom		18x
Iris, F		1.5-3.6
Angle of View, °	Horizontal	55.4-2.9
	Vertical	37.4-1.5
lens Type	Aspherical	-
	Spherical	+
Lens mount		M12
Control		Auto
IR LED		
Distance, m		Up to 100
Number of LEDs, pcs.		9
Beam Spread, °		60
Wavelength, nm		850
IR Cut Filter		Auto
Network		
Network Interface		RJ-45 (10/100Base-T)
Network functions		Cloud/NiP/DDNS/IPFilter/E-mail/NTP/PPPoE/UPNP/FTP/RTSP
Browser supported		Internet Explorer, Opera, Mozilla Firefox, Google Chrome
Languages supported		English, Russian, Arabic, French, Poland, Romanian, Hungarian, Italian
Default IP address		DHCP(Auto)
Username		Admin
Password		Empty by default
HTTP port		80
ONVIF port		8899
RTSP port		554
RTSP string		rtsp://192.168.1.10:554 /user=admin&password=&channel =1&stream=0.sdp?
Control port		34567
Software supported	Free	CMS Partizan
Mobile software	iOS	Partizan CCTV, Partizan Cloud, Partizan Pro
	Android	Partizan CCTV, Partizan Cloud, Partizan Pro
System Integration		Partizan SDK, ONVIF 2.4+
Dimensions		
Size, mm	Total length	-
	Housing	Ø208x443
	Bracket	-
Weight, g		4200
Common		
Power Supply	DC V/A	12/5
	PoE, Class/W	-
Alarm	Inputs	-
	Outputs	-
Audio	Inputs	-
	Outputs	-
Memory card		+
Housing material		Metal
Bracket material		Metal
IP rating		66
IK rating		-
Operating temperature, °C		-40 - +60
Warranty, years		3